

Prilog / Attachment

TE-20147

Catalyst Activator (Top) type "K" dual temperature element (thermocouple) c/w 3/4" S.S. npt connection.

K-125-316-D-0202.7-A-99F-YM2-0036-S9

Type 'K' Duplex Thermocouple

- 5149 mm length Insertion from end of Fitting
- Explosion Proof Aluminum Head (IEC Ex d IIB, T3)
- 914 mm Armored Extension
- c/w SST Compression Fitting and Bushing providing a 3/4" MNPT Process connection
- Head: IME 14-1080S ATEX Approved Head ATEX II 2GD Ex d IIC Gb Ta = -40°C to 85°C, Ex tb IIIC Db IP68
- Electrical Conduit Connection: 1/2"-14 NPT

TE-20149

Catalyst Activator (Bottom) type "K" dual temperature element (thermocouple) c/w 3/4" S.S. npt connection.

K-125-316-D-0395.7-A-99F-YM2-0036-S9

Type 'K' Duplex Thermocouple

- 10052 mm length Insertion from end of Fitting
- Explosion Proof Aluminum Head (IEC Ex d IIB, T3)
- 914 mm Armored Extension
- c/w SST Compression Fitting and Bushing providing a 3/4" MNPT Process connection
- Head: IME 14-1080S ATEX Approved Head ATEX II 2GD Ex d IIC Gb Ta = -40°C to 85°C, Ex tb IIIC Db IP68
- Electrical Conduit Connection: 1/2"-14 NPT